Can-am. OUTLANDER MAX DPS 450/570

HIGHLIGHTS

- Rotax[®] engine options
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- Double A-arm front suspension
- Torsional Trailing arm Independent (TTI) rear suspension
- Visco-Lok[†] QE auto-locking front differential
- 5.4 gal (20.5 L) fuel capacity
- 1,300 lb (590 kg) towing capacity
- 12 in. cast-aluminum wheels
- · Heavy-duty front bumper
- 500 W magneto
- Multifunction digital gauge
- Steel racks with LinQ quick-attach accessory system and a combined 360 pounds (163.3 kg) capacity
- · 2.9 gal (10.9 L) water-resistant rear compartment



Tundra Green / 450 / 570

_.....

450	570	
38 hp, Rotax 427 cc single cylinder, liquid-cooled	48 hp, Rotax 570 cc V-twin, liquid-cooled	
Electronic Fuel Injection (EFI)		
CVT, P/R/N/H/L, standard engine braking		
Selectable 2WD/4WD with Visco-Lok QE auto-locking front differential		
Tri-Mode Dynamic Power Steering (DPS)		
	38 hp, Rotax 427 cc single cylinder, liquid-cooled Electronic Fuel CVT, P/R/N/H/L, star Selectable with Visco-Lok QE auto-	

SUSPENSIONS

Front Suspension	Double A-arm 9 in. (22.9 cm) travel	
Front Shocks	Oil	
Rear Suspension	Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel	
Rear Shocks	Oil	

TIRES & WHEELS

Front Tires	Carlisle Trail Wolf 25 x 8 x 12 in.
Rear Tires	Carlisle Trail Wolf 25 x 10 x 12 in.
Wheels	12 in. cast-aluminum

BBUKES

BIUILEO	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

DIMENSIONS & CAPACITIES	450	570	
Estimated Dry Weight*	715 lb (324 kg)	741 lb (336 kg)	
LxWxH	91 x 46 x 52.5 in. (231 x 116.8 x 133 cm)		
Wheelbase	59 in. (149.9 cm)		
Ground Clearance	10.5 in. (26.7 cm)		
Seat Height	33.8 in. (85.8 cm)		
Rack Capacity	Front: 120 lb (54.4 kg)	Front: 120 lb (54.4 kg)/Rear: 240 lb (109 kg)	
Storage Capacity	Rear: 2.9 gal (10.9 L)		
Towing Capacity	1,300 lb (590 kg)		
Fuel Capacity	5.4 gal (20.5 L)		
Gauge	 4.5 in. digital display: speedometer, tachometer, odometer, trip and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge and clock 		
Instrumentation	Lighter-type DC outlet in console, standard connector in the back (15 A)		
Anti-Theft System	N/A		
Lighting	70 W from dual 35 W	front light/brake light	
Winch	Prewired for available winch		
	Convertible Rack System (CRS)		
Seat	Convertible Rac	sk oystern (onto)	

Factory Warranty	6-month BRP limited warranty	
Extended Service Terms	B.E.S.T. term available up to 36 months	

© 2021 Bombardier Recreational Products Inc (BRP). All rights reserved. @, TM and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. "Base model dry weight shown.", Visoo-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, since, design, features, models or equipment without incurring any obligation. Ride responsibly, BRP highly recommends that all ATV drivers take a training ourse. For safety and training information, see your dealer or, in the U.S.A. all the ATV Safety Institute at 1-800-887-2887. In Canada, call the Canadian Safety Council at 1-613-739-1535, ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding, alcohol and drugs don't mix. Never ride on paved surfaces or public roads. Never regoage in stund triving: Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90 cc are recommended for use only by those age 16 and older. Never crary passengers on any ATV not specifically designated for such use.

